



Fork Lift Grab STAZ-S-4

- ▶ The same characteristics as the STAZ but equipped with a **four-sided clamping action**.
 - ▶ Specially designed for the safe gripping of un-strapped and un-compressed stacks of multi-layer production.
- Because the main and the end gripping is hydraulically controlled separately, and by using pressure plates (accessory!), an exact

compression of the stacks and the elimination of any gaps are achieved.

Two separate hydraulic circuits are necessary to be supplied by the fork lift truck. (Supplied without connecting hoses to the fork lift truck).

To set the length of the grippers exactly, we need you to send us drawings of the mold layouts together with your order.

Type	Opening Width Main Gripper W1 mm (in)	End Gripper W2 mm (in)	Height E mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
STAZ-S-4-850	550 – 1,230 (21¾ – 48")	900 – 1,400 (35½ – 55")	850 (33½")	3,000 (6,600)	740 (1,630)	5700.0106
STAZ-S-4-1000	550 – 1,230 (21¾ – 48")	900 – 1,400 (35½ – 55")	1,000 (39")	3,250 (7,150)	780 (1,720)	5700.0109
STAZ-S-4-1200	550 – 1,230 (21¾ – 48")	900 – 1,400 (35½ – 55")	1,200 (47")	3,500 (7,700)	890 (1,960)	5700.0149

Pressure Plates see page 11.8

Larger or modified opening widths and heights are available on request.

Selective Layer Clamp STAZ-SLC

Specially designed to help select one or several layers of stones with a fork lift truck.

- ▶ Has an integrated, adjustable height stop, controlled by the gripping function, only one hydraulic circuit is necessary.
- ▶ Adjustable height stop is being controlled by a scissor system – it therefore reduces the necessary space required.

▶ Low maintenance Steel–Polyamide–Sliding Guide (without connecting hoses to the fork lift truck, without fork sleeves and without rubber grippers, see accessories).

Standard specification:

- ▶ Manually adjustable pressure relieve valve
- ▶ Oil Pressure Gauge

Type	Opening Width W1 (mm) (in)	Height E (mm) (in)	Working Load Limit WLL kg (lbs)	Dead Weight (kg) (lbs)	Order-Number
STAZ-SLC	370 – 1.370 (14½ – 54")	500 (700) (19¾) (27½")	1.500 (3.300)	310 (680)	5705.0015

Recommended Accessories:

Type	(Description see pages 11.7, 11.8, and 11.12)
Gripping Elements:	
Rubber Grippers	see page 11.7
Steel Finger Grippers	see page 11.8
Hydraulic connection hoses	see page 11.12