



Sorting Clamp ASZ/ASZ-R

This univeral outsorting clamp has a wide adjustable opening width and can be used for a wide range of products.

There are two different variations:

1. ASZ for the efficient outsorting of concrete steps, kerb stones and similar.

2. ASZ-R for the handling of sewerage elements. The grippers are prism-shaped to grip the round contour of the rings.

Standard Specifications:

- ▶ Lifting eye for attaching to crane hook
- ▶ Lifting handle

▶ Handle with turning range 90° depending on space.


Exchangeable rubber metal bars, to suit the requirements.

▷ Automatic release for fully automatical switch-over from "full" to "empty".

Please note:

Designed and suitable to grip single stones or elements only. This is not the proper equipment for handling a complete row of stones.

| Туре | Pack width W mm (in) | Inside Height mm (in) | Gripper Length L mm (in) | Working Load Limit WLL kg (lbs) | Dead Weight kg (lbs) | Order-Number | | | |
|--------------|--|--------------------------|---|------------------------------------|-------------------------|---------------|--|--|--|
| ASZ ⁰ | 600 – 1,200 (23 ¹ / ₂ – 47") | 120 (4³/₄″) | 200 (7 ^{3/4} ") | 250 (550) | 26 (55) | 5310.0259-005 | | | |
| Addition | Additional adapters for ASZ (to be mounted on the basic grippers of the outsorting clamp). | | | | | | | | |
| A-50 | | | 50 (2") | | | 4310.0376 | | | |
| A-100 | | | 100 (4") | | | 4310.0377 | | | |
| ASZ-R● | Ø 620 − 1,200 (231/₂ − 47″) | 100 (4″) | 300 (11 ₃ / ₄ ") | 250 (550) | 34 (75) | 5310.0281-003 | | | |



Pneumatic Sorting Clamp ASZ-P

This universal outsorting clamp offers a versatile use due to large adjustable opening width. Optimum for slabs, kerb stones and wall-rings for plants, etc.

Suitable for attachment to a vacuum lifting unit or to a overhead or jib crane.

Cylinder lifting 150 mm: the further range of opening width is mechanically adjustable.

| C. 1 | | • | | | |
|-------|-----|-----|-------|------|-----|
| Stand | ard | Spe | citic | atio | ns: |

 \triangleright With flange plate to attach to a vacuum lifting unit.

Pneumatic closing cylinder and additional manual adjustment to achieve a larger opening width.

 \triangleright Hand-guided valve with closing cylinder.

| Туре | Opening Width gripping inside mm (in) | Opening Width gripping outside mm (in) | Working Load Limit WLL kg (lbs) | Dead Weight kg (lbs) | Order-Number |
|-------|--|---|------------------------------------|-------------------------|--------------|
| ASZ-P | 270 - 600 (10 ³ /4 - 23 ¹ /2") | 220 - 1,050 (8³/4 - 41″) | 120 (265) | 18 (40) | 5740.0023 |

Other opening widths and heights are available on request.