



## Plasterboard Grabs GPZ

Specially designed for gripping and handling gypsum wall elements.

The grab type GPZ-M-66-120 is a fully mechanical operated unit and can be attached to any truck mounted crane (without hydraulic connections). An appropriate leverage produces high clamping force for safe handling. (Hydraulic rotator see type list, page 15.7)

Low profile construction so that the grab, along with the plasterboard wall sections, can be passed through the window opening.

► An appropriate leverage produces high clamping force for safe handling.

Height measurement from top of pack until top edge of crane-eyelet only 415 mm (16 1/2") (in clamped position).

► Low gap requirement on one side (25 mm).

### Standard Specifications:

- Lifting eye for crane hook.
- Automatic release for the fully automatic switch over from "full" to "empty".
- Highly durable, replacable rubber metal bars for gripping.

Type	Suitable for pack width* W mm (in)	Height E mm (in)	Gripper Length L mm (in)	Working Load Capacity kg (lbs)	Dead Weight kg (lbs)	Order-Number
<b>GPZ-M-66-120</b>	670 (26 1/2")	220 (8 3/4")	1,200 (47")	600 (1,320)	115 (255)	<b>5630.0008</b>

Other opening ranges and heights on request.

The Gypsum Block Grab GPZ-H is hydraulically adjustable (with additional mechanical bolt adjustment).

The strong rack equalizer guarantees a constant working of the hydraulic cylinders.

► The total height of hydraulic rotator incl. suspension is only ca. 450 mm.

Type	Opening Width* W mm (in)	Height E mm (in)	Gripper Length L mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
<b>GPZ-H</b>	480 – 870 (19 – 34 1/4")	140 (5 1/2")	1,200 (47")	600 (1,320)	140 (310)	<b>5630.0007</b>

\* Possible measurement between the grippers. The product measurements must be within approx. ± 30 mm within the given range.

Grab can be equipped with security net on demand.



## Manhole Polyp SP-H

Grips from the inside for the transportation of manhole rings and cones. Manually presetting and hydraulically adjustable for internal diameters up to 2,000 mm.

Allows up to 3 rings to be lifted at the same time.

Not suitable for green products.

### Standard Specifications:

- Manually adjustable pressure control valve.
- Exchangeable rubber grippers for the gentle handling of rings or cones.

Type	Gripping Range ID mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
<b>SP-H</b>	500 – 2,000 (19 3/4 – 79")	2,000 (4,400)	165 (365)	<b>5720.0056</b>