











Alignment Bar RE

For aligning the paving stones before they are permanently set.

▶ With two handles, a foot bar and a hammering surface to drive it into the paver joints using a hammer.

▶ With exchangeable, robust, sharp-edged hardened spring steel blade for driving into the hinge joints.

▶ Durable galvanized surfaces.

Туре	Dead Weight kg (Ibs)	Order-Number
REO	1,5 (3.3)	5180.0011
Spare blade for RE/MRE per piece, loose	0,14 (0,3)	4180.0002
Spare blade for RE/MRE 1 piece in blister pack	0,16 (0,3)	4180.0241

Multiple Alignment Bar MRE

The "Turbo Accelerator" for alignment work: Instead of moving only one row of pavers, the MRE can move 4 or up to 5 rows at the same time. Alignment work is done 4 - 5 times quicker!

Especially suitable for alignment work on mainly rectangular shaped pavers

▶ With 4 exchangeable, adjustable, sturdy, sharp edged hardened spring steel blades.

▶ With 2 handels and one hammering surface to drive it into the paver joints by hammer.

Durable galvanized surfaces.

German Patent

MRE [®] 650 (25	6 (13)	5180.0045

Adapter or special designs for dentated pavers (e.g. Uni pavers) on request.

Rubber Hammer GH

For aligning the paving stones before they are permanently set.

Light-weight, available with long or short handle for work in optimal position.

▷ With easily exchangeable, highly wear resistant replaceable rubber caps.

▶ The hammer remains vertical after use because of the rectangular shape of the rubber caps.

Туре	Lenght of handle mm (in)	Dead weight kg (lbs)	BestNr.
GH	800 (31 ¹ /2 ["])	2,2 (5)	5180.0012
GH-K	400 (15 ³ /4")	1,8 (4)	5180.0051
Rubber cover for GH/GH-K		per piece	4180.0006

Paver Set

Consisting of Paving Block Extractor, Alignment Bar and Rubber Hammer GH	5180.0014
--	-----------

• Durable surface protection by galvanizing