

NEW: Working Load Limit

200kg




Vacuum Handheld Devices

VACUUM LAYING

5





with VS-SWV-SPS-50-30/25 + VS-GH-SPS-140-70/30



• Durable surface protection by galvanizing

SPEEDY VS-140/200 Vacuum Hand Laying Device

With this new inexpensive hand laying tool all kinds of slabs can be layed quickly and above all, ergonomically.

The powerful single phase powered vacuum turbine also allows the auick and safe handling of very porous material as well as material with exposed aggregat surface.

▶ NEW: Can now, when combined with the corresponding suction plate and lifting eye VS-EH safely lift and lay elements weighing up to 200 kg.

▶ The working load limit with handles is 140 kg. ▶ The construction of the SPEEDY has been reinforced throughout.

▶ Quick positive suction action (0.5 sec).

▶ Handles individually height adjustable. Important for users of different heights and for laying steps.

▶ Two short handles (in lower position) make easier the taking-off from high stacks of slabs.

Special suction plate exchangeable for spe- \triangleright cial elements with maximum weight of 200 kg.

▶ The handles can be folded down for easy transportation (see picture).

▶ Light weight design - only approx. 18 kg dead weight. ▶ Galvanised.

SPEEDY VS-XL

with long handles for safe installation of slabs

with lifting eye and safety chain for risk-free lifting and handling

NEW: Quick Change device with integral suction plate VS-SWV-SPS-50-30/25

▶ The SWV Quick Change device is simply screwed onto the SPEEDY VS-140/200 in place of the standard suction plate. This allows elements up to 50 kg weight to be lifted and laid. The former VS-SPS-50-30/25 suction plate then becomes superfluous as it is now integrated.

▶ The SWV Quick Change device allows all new standard suction plates to be mounted in seconds without using tools via 2 quick-change locks.

▶ The SWV can also be retro-mounted on the earlier SPEEDY-VS-140; existing suction plates must then be retro-fitted with 2 screw-fitted hooks.

▶ The SWV can also be moved through 90 degrees before being screwed onto the SPEEDY; thus allowing the standard suction plates to be used in any preferred alignment.

Vacuum Hand Laying Device SPEEDY VS Basic Devices Туре Working Load Limit Dead Weight Order-Number Power Description WLL kg (lbs) kg (lbs) VS-140/200 • electrically 230 Volt depending on size without suction plate 5270.0011 18 **Basic Device**** single phase 50 Hz of suction plate with standard handle (40) VS-140/200-XL electrically 230 Volt depending on size 23 without suction plate 5270.0012 with long handle lifting eye, safety chain Basic Device •** single phase 50 Hz of suction plate (51) VS-140/200- • electrically 110 Volt depending on size 18 without suction plate 5270.0013 110 Basic Device single phase 50/60 Hz of suction plate (40)with standard handle electrically 110 Volt without suction plate VS-140/200-XL^① depending on size 23 5270.0014 with long handle lifting eye, safety chain -110 Basic Device single phase 50/60 Hz of suction plate (51)

SPEEDY POWER-RACK VS-PR

Holder for practical storing of the EU 20i Honda generator when operating the SPEEDY on lifting equipment (e.g. a digger).

 \triangleright No cumbersome cable to consider.

▶ VS-PR is simply hung on the carrying device with adjusted generator. The VS-EH* lifting eye of the SPEEDY is then hung on the eye hook of the VS-PR.

 \triangleright In the case of a carrying device with a large lifting height, the eye hook may be connected to the VS-EH* lifting eye with the 2 m long loop supplied. Thus, first the SPEEDY then the VS-PR can be switched off.

▶ Incl. 3 m extension cable + Velcro strap.

| Туре | Working Load Limit WLL kg (Ibs) | Dead Weight kg (Ibs) | Order-Number |
|---|---------------------------------|----------------------|--------------|
| VS-PR ^O | 200 (440) | 10 (20) | 4271.0149 |
| * Not included in the scope of delivery of VS-140/200 (-110) (cf. p. 5.7) ** Plug type F, 230 V | | | |