




# FTZ-MULTI-15 53100348 43100942 43100943 43100941





# **Grab for Prefabricated Concrete Products FTZ-MULTI**

Innovative, mechanical grab. Appropriate clamp configurations for versatile applications from a modular construction system.

Same features as per FTZ-I/UNI.

Extraordinary large gripping range, thus suitable for gripping nearly all kind of standard concrete elements and natural stones.

The individual modules are available separately and hence a huge range of applications can be covered at a reasonable price (base body + 3 sets of grippers cover the entire spectrum!)

FTZ-MULTI-15: Basic unit without grippers

**► WB-G-42:** Large gripping range, short rubber grippers - preferably suitable for handling of single elements.

**▶ WB-G-120:** Large gripping range, large rubber grippers - preferably suitable for hand-

ling of full layers, such as one layer of kerb stones etc.

**WB-SQ:** Special interlocking steelfinger grippers allow for safe installation of roughly-cut ashlar rocks.

## **Components for Optional Clamp Configuration**

Туре	Gripping Range* W mm (in)	Inside Height E mm (in)	Gripper Lenght L mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
FTZ-MULTI-15				1,500	96	5310.0348
Basic Device®				(3,300)	(210)	
FTZ-MULTI-15-	200 - 1,250	255	420		14	4310.0942
<b>WB-G-42 (</b> pair)	(8-49")	(10")	(161/2")		(30)	
FTZ-MULTI-15-	200 - 1,250	255	1,200		46	4310.0943
<b>WB-G-120 (</b> pair)	(8 – 49")	(10")	(47")		(100)	
FTZ-MULTI-15-	200 – 1,200	300			33	4310.0941
WB-SQ <sup>®</sup> (pair)	(8 – 47")	(12")			(75)	

### Acessories

Adapter for Kassel Kerb Stone A-FTZ-KB <sup>®</sup> for FTZ-UNI-15 to extend gripping depth on one side to 290 mm	4310.0575
Adjustable Height Stop HVA-FTZ/TSZ® for all versions of FTZ-UNI/MAXI/MULTI and TSZ-UNI. Adjustable range approx. 140 — 255 mm. Adjustable range FTZ-UNI/MAXI-15 and FTZ-UNI-25 approx. 120 — 255 mm. FTZ-UNI-40 approx. 55 — 155 mm. FTZ-MAXI-40 approx. 55 — 195 mm.	4310.0867

# **Grab for Prefabricated Concrete Products FTZ-MULTI-D**

Modularly designed grab — with even larger inside height.

A single clamp top with screw-on grippers for the broadest range of tasks. Maximum application options due to large gripping range with low acquisition costs. The FTZ-MULTI-15-D basic device can be fitted with the same clamps as are suitable for the FTZ-MULTI-15 (see description above).

Туре	Gripping Range* W mm (in)	Inside Height E mm (in)	Gripper Lenght L mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
FTZ-MULTI-15-D Basic Device <sup>©</sup>				1,500 (3,300)	140 (310)	5310.0393
FTZ-MULTI-15- WB-G-42 (pair)	0 – 750 (29½")	540 (21")	420 (16½")		14 (30)	4310.0942
FTZ-MULTI-15- WB-G-120 <sup>©</sup> (pair)	0 – 750 (29½")	540 (21")	1,200 (47")		46 (100)	4310.0943
FTZ-MULTI-15- WB-SQ <sup>•</sup> (pair)	0 – 700 (27½")	585 (23")			33 (73)	4310.0941

<sup>\*</sup>Gripping range indicates the minimum and maximum pack measurements of building materials, which can be picked-up with this grab.

1/2019 - 6.5

<sup>•</sup> Durable surface protection by galvanizing