



## Grab for Angular Concrete Products WEZ

Specially developed for handling L-stones and similar products. The lifting eye can be adjusted to the center of gravity of all prevalent products being lifted to let it hang vertically.

### Standard Specifications:

- ▶ Lifting eye for attaching to crane hook.
- ▶ Highly durable and exchangeable rubber grippers.
- ▶ Automatic release for the fully automatic change over from "full" to "empty".
- ▶ Leaves no black marks.

Type	Gripping Range* W mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
<b>WEZ-2 ①</b>	50 – 250 (2" – 9¾")	2,000 (4,400)	55 (120)	<b>5310.0347</b>
<b>WEZ-6 ①</b>	50 – 300 (2" – 11¾")	6,000 (13,200)	160 (350)	<b>5310.0375</b>



## Mechanical Boulder Grab FVZ-UNI

Suitable for handling boulders. Stones of almost all shapes can be lifted and laid to the exact millimetre. ▶ With chains (by changing the chain-position,

the clamp can be lifted after setting of the stone). ▶ Automatically adjustable gripping range from 0 to a maximum of 950 mm. ▶ With lifting eye for attaching to crane hook.

Type	Gripping Range* W mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
<b>FVZ-UNI</b>	0 – 950 (0 – 37½")	1,500 (3,300)	99 (218)	<b>5310.0272</b>



## Manual Boulder Grab H-FVZ-UNI

A manual boulder grab for smaller boulders which can be carried by two men. ▶ Additionally equipped with a ring-eyelet to be hooked onto any kind of lifting device,

regarding the admissible working load limit. ▶ Equipped with a simple and fast gripping range adjustment. ▶ Galvanised finish

Type	Gripping Range* W mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
<b>H-FVZ-UNI ①</b>	0 – 600 (0 – 23½")	200 (440)	18 (40)	<b>5320.0086</b>



## Flat Grab FZ

FZ for transport of slabs. ▶ Narrow grippers turn standing slabs or erect laying slabs. ▶ No problem to grip even tight standing slabs. ▶ No damage to the surface of the slabs due to gentle handling with rubber grippers.

▶ High security by enormous transmission of 5:1. ▶ A spring tension prevents from unintentional slipping off the clamp. ▶ Lifting band instead of chain or rope: low dead weight, no squeezing, no hurts. ▶ Suitable for nearly all kinds of material.

Type	Gripping Range* W mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
<b>FZ</b>	0 – 60 (0 – 2½")	800 (1,760)	6 (13)	<b>5310.0278</b>

\*Gripping range indicates the minimum and maximum pack measurements of building materials, which can be picked-up with this grab.

① Durable surface protection by galvanizing