



Round Grab RG

Specially for laying sewer pipes.
Wider gripper arms mean that coated pipes are not damaged.
▶ Can be used in narrow ditches as little room is needed on either side for the grab to work.

- ▶ Large opening range
- ▶ Mechanically operated

Standard Specifications:

- ▶ Crane eye for attaching to crane hook.
- ▶ No additional operating personnel are needed.

Type	Outer Diameter of Pipes D mm (in)	Gripper Length mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
RG-1,5-47	200-470 (7 3/4 - 18 1/2")	430 (17")	1,500 (3,300)	56 (125)	5430.0009
RG-1,5-80	300-800 (11 3/4 - 31 1/2")	350 (13 3/4")	1,500 (3,300)	90 (200)	5430.0007
RG-5-150	600-1,500 (23 1/2 - 59")	500 (19 3/4")	5,000 (11,000)	390 (860)	5430.0008
RG-10-200	1,000-2,000 (39 - 79")	750 (29 1/2")	10,000 (22,000)	1,080 (2,380)	5430.0006
RG-12-250	1,500-2,500 (59 - 98")	750 (29 1/2")	12,000 (26,450)	1,450 (3,200)	5430.0004



Manhole and Cone Chain Clamp SRG

For transporting manhole rings and cones.
New: Manhole and Cone Chain Clamp SRG-UNI, especially easy handling and light-weight. Automatically adjustable clamping range of the claws to the thickness of the pipe walls.

- ▶ SRG-UNI-1,5 for manhole rings as per DIN 4034, part 2 and cones.
- ▶ SRG-UNI-3 for manhole rings as per DIN 4034, part 1 + 2 and cones.
- ▶ SRG-1,5, SRG-3, SRG-3-L and SRG-4 are equipped with robust high-tensile lifting chains. Suitable for manhole rings as per DIN 4034 part 2.

Type	Lifting Strap	High-tensile Lifting Chain	Nominal Value ID of cones and manholes mm (in)	Number of Claws	Gripping Range of Claws mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
SRG-UNI-1,5	x		800 - 2,000 (31 1/2 - 79")	3	40 - 120 (1 1/2 - 4 3/4")	1,500 (3,300)	28 (62)	5440.0015
SRG-UNI-1,5-K		x	800 - 1,200 (31 1/2 - 47 1/4")	3	40 - 120 (1 1/2 - 4 3/4")	1,500 (3,300)	33 (73)	5440.0018
SRG-UNI-3	x		800 - 2,000 (31 1/2 - 79")	3	60 - 180 (2 1/4 - 7")	3,000 (6,600)	40 (88)	5440.0014
SRG-UNI-3-K		x	800 - 2,000 (31 1/2 - 79")	3	60 - 180 (2 1/4 - 7")	3,000 (6,600)	45 (99)	5440.0019
SRG-1,5	x		400 - 2,000 (15 3/4 - 79")	3	40 - 120 (1 1/2 - 4 3/4")	1,500 (3,300)	31 (70)	5440.0001
SRG-3	x		400 - 2,000 (15 3/4 - 79")	3	50 - 180 (2 - 7")	3,000 (6,600)	53 (115)	5440.0002
SRG-3-L	x		400 - 3,000 (15 3/4 - 118")	3	50 - 180 (2 - 7")	3,000 (6,600)	57 (125)	5440.0003
SRG-4	x		1,000 - 3,000 (39 1/2 - 118")	4	50 - 180 (2 - 7")	4,000 (8,800)	82 (181)	5440.0020



Manhole Ring Grab Automatic MRGA-80/250

The one-man device for quick, gentle and safe handling of concrete shaft rings (DIN 4034 part 1+2).

- ▶ Can be used on any lifting device, such as a crane, forklift or similar.

▶ Universally adjustable for shaft rings of nominal diameter from 800 to 2,500 mm and for wall thicknesses from 90 to 200 mm.

Standard Specifications:

- ▶ Lifting eye for attaching to crane hook.
- ▶ Automatic release for fully automatic switch over from "full" to "empty".

Type	Nominal Value ID of cones and manholes mm (in)	Number of Claws	Gripping Range of Claws mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
MRGA-80/250	800 - 2,500 (31 1/2 - 98")	3	90 - 200 (3 1/2 - 7 3/4")	3,000 (6,600)	205 (450)	5720.0195



021218 Technical data contained in this catalogue can be modified without prior notice in the interest of progress. Illustrations are exemplary and non-binding. No liability accepted for any misprints, mistakes and errors.