



## R550C5

Engine ref.	6136CG550
Rehlko Alternator description	KH02310T
Canopy	M5228
Performance class	G3

### GENERAL CHARACTERISTICS

Frequency (Hz)	50 Hz
Voltage (V)	400/230
Standard Control Panel	APM403

Voltage	ESP		PRP		Standby Amps
	kWe	kVA	kWe	kVA	
400/230	440	550	400	500	794

### DESCRIPTIVE

- Stage V engine
- Four-pole circuit breaker
- Connection terminal box rental type
- Containment fuel tank and large autonomy
- Forks and frame protection pads
- Adjustable earth fault protection and earthing rod
- Inlet air preheating
- Battery isolating switch
- Oil drainage pump
- Heavy duty air filter with interchangeable cartridge
- Primary fuel filter
- Heat hand protections (EC standards)
- Sockets pack : 1x32A 400V - 1x16A MONO indus  
- 1xMONO SCHUCCO
- Electronic governor with speed adjustment
- Access door to the radiator

### DIMENSIONS

Length (mm)	5000
Width (mm)	1611
Height (mm)	2606
Dry weight (kg)	6460
Tank capacity (L)	1280

### SOUND LEVELS

Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	82
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP) (Associated uncertainty)	73
Sound power level guaranteed (Lwa) 50Hz (75% PRP) (Associated uncertainty)	102 (0.9)

### POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

### TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPa (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

### ASSOCIATED UNCERTAINTY

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.



## R550C5

### ENGINE CHARACTERISTICS

#### GENERAL ENGINE DATAS

Engine brand	JOHN DEERE
Engine ref.	6136CG550
Air inlet system	Turbo
Cylinder configuration	L
Number of cylinders	6
Displacement (l)	13.55
Charge Air coolant	Air/Air
Bore (mm) x Stroke (mm)	132 x 165
Compression ratio	15.9 : 1
Speed 50Hz (RPM)	1500
Pistons speed (m/s)	8.25
Maximum stand-by power at rated RPM (kW)	505
BMEP @ PRP (bar)	27.30
Governor type	Electronic

#### COOLING SYSTEM

Radiator & Engine capacity (l)	61.10
Fan power 50Hz (kW)	20
Type of coolant	Glycol-Ethylene

#### EMISSIONS

Emissions PM (g/kW.h)	0.00065
Emissions CO (g/kW.h)	0.001
Emissions NOx (g/kW.h)	0.079
Emissions HC (g/kW.h)	0.006

#### DIESEL EXHAUST FLUID

DEF Tank Capacity (L) Fuel	113
Cons. @ ESP Max Power (l/h)	5.0
Cons. @ PRP Max Power (l/h)	4.9
Cons. @ 75% of PRP Power (l/h)	3.9
Cons. @ 50% of PRP Power (l/h)	4.3

#### EXHAUST

Exhaust gas temperature @ ESP (°C)	442
Exhaust gas flow @ ESP (l/s)	940
Max. exhaust back pressure (mm H2O)	2243

#### FUEL

Fuel consumption @ ESP Max Power (l/h)	119.50
Fuel consumption @ PRP Max Power (l/h)	109.10
Fuel consumption @ 75% of PRP Power (l/h)	78.70
Fuel consumption @ 50% of PRP Power (l/h)	53.30

#### OIL

Oil system capacity including filters (l)	68
Min. oil pressure (bar)	2.80
Max. oil pressure (bar)	3.80
Oil sump capacity (l)	65

#### HEAT BALANCE


Radiated heat to ambient (kW)	250
Heat rejection to coolant HT (kW)	250

#### AIR INTAKE

Max. intake restriction (mm H2O)	625
Combustion air flow (l/s)	532

Rehiko Alternator description	KH02310T	Continuous Nominal Rating 40°C (kVA)	500
Number of Phase	Three phase	Standby Rating 27°C (kVA)	570
Power factor (Cos Phi)	0.80	Efficiencies 100% of load (%)	94.80
Altitude (m)	0 à 1000	Air flow (m3/s)	0.90
Overspeed (rpm)	2250	Short circuit ratio (Kcc)	0.3480
Number of pole	4	Direct axis synchro reactance unsaturated (Xd) (%)	366
Capacity for maintaining short circuit at 300% of rated current for 10 s	Yes	Quadra axis synchro reactance unsaturated (Xq) (%)	187
Insulation class	H	Open circuit time constant (T'do) (ms)	1968
T° class (H/125K), continuous 40°C	H / 125°K	Direct axis transient reactance saturated (X'd) (%)	18.60
T° class (H/163K), standby 27°C	H / 163°K	Short circuit transient time constant (T'd) (ms)	100
AVR Regulation	Yes	Direct axis subtranscient reactance saturated (X''d) (%)	10.70
Total Harmonic Distortion in no-load DHT (%)	<1.5	Subtranscient time constant (T''d) (ms)	10
Total Harmonic Distortion, on linear load DHT (%)	<2	Quadra axis subtranscient reactance saturated (X''q) (%)	13.60
Wave form : NEMA=TIF	<50	Subtranscient time constant (T''q) (ms)	10
Wave form : CEI=FHT	<2	Zero sequence reactance unsaturated (Xo) (%)	0.70
Number of bearing	Single Bearing	Negative sequence reactance saturated (X2) (%)	12.17
Coupling	Direct	Armature time constant (Ta) (ms)	15
Voltage regulation at established rating (+/- %)	0.50	No load excitation current (io) (A)	0.79
Recovery time (Delta U = 20% transient) (ms)	500	Full load excitation current (ic) (A)	3.21
Indication of protection	IP 23	Full load excitation voltage (uc) (V)	33.50
Technology	Brushless	Engine start (Delta U = 20% perm. or 30% trans.) (kVA)	1287.64
		Transient dip (4/4 load) - PF : 0,8 AR (%)	13
		No load losses (W)	4910.90
		Heat rejected to ambient air (kW)	21.58
		Unbalanced load acceptance ratio (%)	70

APM403, basic generating set and power plant control



The APM403 is a versatile control unit which allows operation in manual or automatic mode  
 Measurements : voltage and current  
 kW/kWh/kVA power meters  
 Standard specifications: Voltmeter, Frequency meter.  
 Optional : Battery ammeter.  
 J1939 CAN ECU engine control  
 Alarms and faults: Oil pressure, Coolant temperature, Overspeed, Start-up failure, alternator min/max, Emergency stop button.  
 Engine parameters: Fuel level, hour counter, battery voltage.  
 Optional (standard at 24V): Oil pressure, water temperature.  
 Event log/ Management of the last 300 genset events.  
 Mains and genset protection  
 Clock management  
 USB connections, USB Host and PC,  
 Communications : RS485 INTERFACE  
 ModBUS protocol /SNMP  
 Optional : Ethernet, GPRS, remote control, 3G, 4G,  
 Websupervisor, SMS, E-mails