designed and created for your needs

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use







more sustainable and environmentally friendly future









4x320W LED - 8,5M







PLUG-IN LINE



APPLICATIONS







FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 8,5 meters vertical tower, 340° rotatable
- Manual lifting system by winch complete with auto-braking system
- Galvanized metalworks
- ≥ 80 µm powder coating
- Very compact dimensions, up to 22 units per truck
- Sites forklift pockets
- Top and sides forklift pockets for effective handling
- Suided main coiled cable to avoid damage during tower operation
- Circuit breaker for electrical protection against overload
- Certified wind stability up tp 110 km/h
- 4 extendable & height adjustable stabilizers
- Inlet plug and outlet socket to connect in series more units

Dimensions & weight

Dimensions min (mm)	1100x1100x2650 (LxWxH)
Dimensions max(mm)	2360x2360x8500(LxWxH)
Total weight (kg)	445
Floodlights	
Туре	Led
Power(each)	320W
Floodlights number	4
IP level	65
Illuminated area (sqm)	9300
Options	Light sensor
Mast	
Lifting method	Manual
Max Height	8,5 m
Max Wind Speed	110 km/h
Rotation	340°
Input&output	
Inlet plug	16A - 230V
Outlet socket	16A - 230V



22 units per truck Safe packaging and loading allowing quick unloading





TRIME[®] Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it